

What is claimed is:

1. An electrical junction box, comprising:
a junction box body; and
a cover which houses and holds the junction box body,
5 wherein a guide rail groove is provided on any one of
an inner surface of the cover and an outer surface of the junction
box body, and a guide rail guided by the guide rail groove
is provided on the other thereof; and
the junction box body is held in the cover at a slant
10 with respect to the guide rail and the guide rail groove.
2. The electrical junction box of claim 1, further
comprising:
a frame provided on a circumference of the junction box
15 body,
wherein any one of the guide rail groove and the guide
rail is provided on an outer surface of the frame.
3. The electrical junction box of claim 2,
20 wherein the guide rail groove is provided on an inner
surface of the cover; and
the guide rail is provided on an outer surface of the
frame.
- 25 4. The electrical junction box of claim 1,
wherein a fuse is mounted on a maintenance surface of

the junction box body.

5. The electrical junction box of claim 2,

wherein an arm lock is provided on the frame, and the
5 arm lock is elastically deformed to be engaged with a projection
of the junction box body so that the frame is attached to the
junction box body.

6. The electrical junction box of claim 1,

10 wherein the guide rail groove includes a straight groove
part and a curved groove part.

7. The electrical junction box of claim 1,

wherein a locking groove is provided on an inner side
15 of the guide rail groove, and a lock projection engaged with
the locking groove is provided on the side of the guide rail,
in order to allow the cover to hold the junction box body.

8. The electrical junction box of claim 1, further

20 comprising:

a wire harness fixing mechanism which fixes a part of
a wire harness, which is connected to the junction box body,
to a side of the junction box body.